



The diagram illustrates the construction of a wall section, specifically focusing on the installation of a new door and window. The wall is shown in cross-section, with various layers and components labeled with numbers and letters.

Top Section: The top of the wall is marked with a horizontal line. Above this line, the number "341" is written on the left, and "112" and "72" are written above the wall's profile. The wall profile shows a series of vertical lines representing different layers or components.

Door Installation: A section of the wall is highlighted in red, indicating the area for a new door. Below this red section, a grey rectangular block represents the door frame. A red curved line indicates the door's swing path. To the right of the door frame, the text "Нова врата" (New door) is written.

Window Installation: Below the door frame, a grey rectangular block represents the window frame. A red horizontal line indicates the window's position. To the right of the window frame, the text "Нов прозорец" (New window) is written.

Textual Description: Below the diagram, there is a block of text describing the construction details:

Преградна стена от гипсокартон на шендерна конструкция
 (1 пл. влагоустойчива гипсокартон 9.5мм + 1 пл. влагоустойчива минерална вата + 1 пл. влагоустойчива гипсокартон 9.5мм)

Външна стена тип тил Кнауф Акваpanel с дебелина 21см

Съществуваща стена

Преградна стена от гипсокартон на щендерна конструкция с двуслойна обшивка (1 пл. влагоустойчив гипсокартон 9.5мм + 1 пл.влагоустойчив гипсокартон 12.5мм + 100мм минерална вата + 1 пл. влагоустойчив гипсокартон 12.5мм + 1 пл.влагоустойчив гипсокартон 9.5мм)

Външна стена тип тип Кнауф Aquarpanel с дебелина 21см

Съществуваща стена

Нова вѣст

Нова прозорца